



Texture Information Sheet

Product | Castello

Description

An acrylic, antique satin translucent glaze for painted or textured surfaces; ideal for application over QuartzSilco, Craquelatto, Sabbia and other PermaTone textures.

Recommended Use

Interior commercial and residential applications to add depth and tonal variation.

Colors

All custom; no limitations.

Packaging

1 gallon pail: 8 lbs. net, 8.7 lbs. gross; 5 gallon pail: 39 lbs. net, 41.8 lbs. gross.

Approximate Coverage

1350-1600 ft² per 5 gallon bucket.

Equipment

Paint roller; cotton towels.

Surface Preparation

Surfaces must be clean and dry. When applied over PermaTone textures, consult the application instructions for such textures for drying and curing times.

Application Instructions

This texture is used in connection with Sabbia Antique Dragged. Work in sections small enough to avoid the material becoming too dry to spread and texture. Roll Castello onto the surface. Immediately dampen the cotton towel and use to evenly spread the material and to achieve the desired uniform thickness. Remove most of the Castello from smooth areas while leaving most of the material on rough areas. Rinse the towel often. Material may be diluted up to 15% with potable water only.

Properties

Initial set in 1 hour, dry in 72 hours, full cure in 30 to 60 days, at 70°F and 50% RH.

Benefits

Water based; integral color; environmentally safe; durable; vapor permeable.

Limitations

Patching limitations standard to applied coatings; skilled application required; not compatible with solvents; apply in temperatures between 60°F and 85°F; protect face and eyes; use in well ventilated areas; for use on interior wall and ceiling surfaces only.

Maintenance

Surface may be cleaned of minor stains with a damp cotton cloth.

Warranty

10 years material warranty against delamination, color fading and mildew growth.

- Always prepare a mock-up of minimum 4' x 4' for approval prior to application to subject wall areas. The mock-up serves two purposes, to establish coverage and material requirements and to establish owner's expectations as to the appearance of the texture. Coverage varies according to substrate conditions and applicator technique and skill level.
- The application instructions described herein represent the most typical methods currently used, but are in no way intended to restrict the designer, contractor or faux finisher in terms of creating new patterns, effects or textures using PermaTone products. Instructions as to surface preparation and reduction should be followed precisely, however, in order not to void the warranty.
- PermaTone products should never be mixed with other materials, with the exception of clean, potable water, and then only where indicated as acceptable in this or other PermaTone product information documents.
- Information contained in this bulletin conforms to the standard detail recommendations and specifications for the installation of PermaTone products, is presented in good faith, and is applicable as of the date of this document. PermaTone assumes no liability, expressed or implied, as to the architecture, engineering, or workmanship of any project.
- Most equipment described in this document may be purchased from PermaTone or its distributors.

Swab