



Texture Information Sheet

Product | Palladio

Description

An acrylic Venetian plaster; medium to high gloss polished marble appearance.

Recommended Use

Interior commercial, hospitality and residential applications requiring dramatic high-gloss accents.

Colors

All custom; no limitations.

Packaging

1 gallon pail: 10 lbs. net, 10.7 lbs. gross; 5 gallon pail: 56 lbs. net, 58.8 lbs. gross

Approximate Coverage

600-900 ft² per 5 gallon bucket.

Equipment

Stainless steel trowel with rounded corners and beveled edges; flexible metallic spatula; sandpaper #100 and #320.

Surface Preparation

Surfaces must be smooth, clean, dry and paint ready. Refer to application instructions for Corevmix.

Application Instructions

Using the specified trowel, apply the first layer using short strokes and irregular patterns. Avoid material buildup. Individual coats should not exceed 9 mils. Allow the first coat to dry 4-6 hours, unless a third coat is to be applied, in which case, second coat may be applied immediately following the first. At least two coats are necessary. The darker the material, the more coats are required. Additional coats add depth to the texture. Once the final coat is applied, immediately polish. When working alone, restrict work to small sections so that the material does not become too dry to polish. If one installer applies and another polishes, larger areas may be underway at one time. To achieve the desired gloss, repeatedly press down and slide the trowel edge over the surface of the final coat, holding a 5-10° angle to the surface. Additional burnishing produces additional gloss, but do not over-burnish the finish. See the texture information sheet for Reflexi Spatula for application instructions of Reflexi. Use PermaWax in areas where exposure to water splash or staining is expected. Review application instructions for PermaWax.

Properties

Initial set in 10 minutes and cure in 72 hours at 70°F and 50% RH.

Benefits

Water based; integral color; environmentally safe; vapor permeable; highly mildew resistant.

Limitations

Patching limitations standard to applied coatings; skilled application required; not compatible with solvents; apply in temperatures between 60°F and 85°F; protect face and eyes; use in well ventilated areas; for use on interior wall and ceiling surfaces only.

Maintenance

Surface may be cleaned of minor stains with a damp cotton cloth.

Warranty

10 years material warranty against delamination and color fading.

- Always prepare a mock-up of minimum 4' x 4' for approval prior to application to subject wall areas. The mock-up serves two purposes, to establish coverage and material requirements and to establish owner's expectations as to the appearance of the texture. Coverage varies according to substrate conditions and applicator technique and skill level.
- The application instructions described herein represent the most typical methods currently used, but are in no way intended to restrict the designer, contractor or faux finisher in terms of creating new patterns, effects or textures using PermaTone products. Instructions as to surface preparation and reduction should be followed precisely, however, in order not to void the warranty.
- PermaTone products should never be mixed with other materials, with the exception of clean, potable water, and then only where indicated as acceptable in this or other PermaTone product information documents.
- Information contained in this bulletin conforms to the standard detail recommendations and specifications for the installation of PermaTone products, is presented in good faith, and is applicable as of the date of this document. PermaTone assumes no liability, expressed or implied, as to the architecture, engineering, or workmanship of any project.
- Most equipment described in this document may be purchased from PermaTone or its distributors.

Spatula