



Texture Information Sheet

Product | **Riflexi**

Description

A decorative pearlescent metallic glaze for almost any surface; produces stunning effects in combination with PermaTone textures.

Recommended Use

Interior commercial, hospitality and residential applications where a dramatic metallic effect is desired.

Colors

9 standard colors.

Packaging

1 gallon pail: 7.4 lbs. net, 8.1 lbs. gross; 5 gallon pail: 39 lbs. net, 41.8 lbs. gross

Approximate Coverage

1500-2000 ft² per 5 gallon bucket.

Equipment

Stainless steel trowel with rounded corners and beveled edges; spatula; knockdown blade

Surface Preparation

Surfaces must be clean and dry. When applied over PermaTone textures, consult the application instructions for such textures for drying and curing times..

Application Instructions

Using a stainless steel trowel, apply Riflexi to the surface using small strokes and an irregular pattern. Avoid material buildup. Thickness should not exceed 5 mils..

Properties

Initial set in 30 minutes, dry in 72 hours, full cure in 30 to 60 days, at 70°F and 50% RH.

Benefits

Water based; integral color; environmentally safe; vapor permeable.

Limitations

Patching limitations standard to applied coatings; skilled application required; not compatible with solvents; apply in temperatures between 60°F and 85°F; protect face and eyes; use in well ventilated areas; for use on interior wall and ceiling surfaces only.

Maintenance

Surface may be cleaned of minor stains with a damp cotton cloth.

Warranty

10 years material warranty against delamination, color fading and mildew growth.

- Always prepare a mock-up of minimum 4' x 4' for approval prior to application to subject wall areas. The mock-up serves two purposes, to establish coverage and material requirements and to establish owner's expectations as to the appearance of the texture. Coverage varies according to substrate conditions and applicator technique and skill level.
- The application instructions described herein represent the most typical methods currently used, but are in no way intended to restrict the designer, contractor or faux finisher in terms of creating new patterns, effects or textures using PermaTone products. Instructions as to surface preparation and reduction should be followed precisely, however, in order not to void the warranty.
- PermaTone products should never be mixed with other materials, with the exception of clean, potable water, and then only where indicated as acceptable in this or other PermaTone product information documents.
- Information contained in this bulletin conforms to the standard detail recommendations and specifications for the installation of PermaTone products, is presented in good faith, and is applicable as of the date of this document. PermaTone assumes no liability, expressed or implied, as to the architecture, engineering, or workmanship of any project.
- Most equipment described in this document may be purchased from PermaTone or its distributors.

Spatula