



Texture Information Sheet

Product | **Sabbia**

Description

A decorative acrylic Venetian plaster reminiscent of travertine.

Recommended Use

Interior commercial, hospitality and residential applications requiring a natural antiqued Travertine appearance.

Colors

All custom; no limitations.

Packaging

1 gallon pail: 11 lbs. net, 11.7 lbs. gross; 5 gallon pail: 60 lbs. net, 62.8 lbs. gross.

Approximate Coverage

150-250 ft² per 5 gallon bucket

Equipment

Hawk; stainless steel trowel with rounded corners and beveled edges; acrylic float; urethane float.

Surface Preparation

Surfaces must be smooth, clean, dry and paint ready. Prime surfaces with Pintufondo in the desired base color. See instructions for application of Pintufondo.

Application Instructions

Using the specified trowel, apply the first layer of Sabbia using short strokes and irregular patterns. Avoid any material buildup. The largest aggregate in the coating will determine the thickness of each coat. Allow to dry 8-12 hours. Apply a second coat in the same manner. Allow the material to dry approximately 30-45 minutes before texturing, depending on room temperature and humidity. Use a urethane float with vertical downward strokes by pressing down and sliding the float's edge, holding a 5-10° angle to the wall, until a light open texture similar to Travertine stone is achieved. Immediately follow with the acrylic float, holding it flat to the surface with light pressure, in order to knock down any excess material and "tighten" the finished look. Material may be diluted with up to 8 ozs. of potable water only per five gallon bucket.

Properties

Initial set in 6 hours, dry in 36 hours, full cure in 30 to 60 days, at 70°F, 50% RH.

Benefits

Water based; integral color; environmentally safe; vapor permeable; highly mildew resistant; highly scratch and abrasion resistant.

Limitations

Patching limitations standard to applied coatings; skilled application required; not compatible with solvents; apply in temperatures between 60°F and 85°F; protect face and eyes; use in well ventilated areas; for use on interior wall and ceiling surfaces only.

Maintenance

To clean, use a medium bristle brush or damp cloth and a mild soap and water solution.

Warranty

10 years material warranty against delamination, color fading and mildew growth

- Always prepare a mock-up of minimum 4' x 4' for approval prior to application to subject wall areas. The mock-up serves two purposes, to establish coverage and material requirements and to establish owner's expectations as to the appearance of the texture. Coverage varies according to substrate conditions and applicator technique and skill level.
- The application instructions described herein represent the most typical methods currently used, but are in no way intended to restrict the designer, contractor or faux finisher in terms of creating new patterns, effects or textures using PermaTone products. Instructions as to surface preparation and reduction should be followed precisely, however, in order not to void the warranty.
- PermaTone products should never be mixed with other materials, with the exception of clean, potable water, and then only where indicated as acceptable in this or other PermaTone product information documents.
- Information contained in this bulletin conforms to the standard detail recommendations and specifications for the installation of PermaTone products, is presented in good faith, and is applicable as of the date of this document. PermaTone assumes no liability, expressed or implied, as to the architecture, engineering, or workmanship of any project.
- Most equipment described in this document may be purchased from PermaTone or its distributors.

Antique Travertine