



Support Product

Description

A permeable, finely ground, acrylic base leveling material.

Recommended Use

Interior commercial, hospitality, military, educational and residential applications; used in connection with PermaTone Walltextures.

Colors

White; may be tinted for use with dark color finishes.

Packaging

1 gallon pail: 12 lbs. net, 12.7 lbs. gross; 5 gallon pail: 60 lbs. net, 62.8 lbs. gross.

Approximate Coverage

200-250 ft² per 5 gallon bucket.

Equipment

Stainless steel trowel or spatula; sandpaper #100 to #320, depending on topcoat material; cotton towel

Surface Preparation

Surfaces must be clean, dry and free of dust, grease or other materials that may affect bonding. Previously painted surfaces must be scraped to remove all loose paint.

Application Instructions

Mix CorevMix to a homogeneous consistency with a mud mixer at low speed. Material may be diluted up to 12 oz. of water per 5 gallon bucket in order to achieve desired consistency. Apply CorevMix with a stainless steel trowel. Allow to dry 4-6 hours to dry and apply as many layers as needed to achieve the required thickness and planarity. When the product is dry, sand the surface to the required smoothness (see application information for such products as Palladio and Tevere). Remove any residual dust before applying any other materials.

Properties

Initial set in 2 hours, cure in 24 hours, at 70°F and 50% RH.

Benefits

Water based; environmentally safe; smooth; vapor permeable; flexible; hard; low absorption.

Limitations

Skilled application required; not compatible with solvent based products or cleaners; apply in temperatures between 60°F and 85°F; protect face and eyes; use in well ventilated areas; for use on interior wall and ceiling surfaces only; do not mix with other products; single coats in excess of 30 mil thickness may cause surface cracking; prepare metal surfaces such as corner bead with rust inhibitor prior to application of CorevMix.

Maintenance

See Application guidelines for PermaTone Walltextures for information on maintenance.

Warranty

10 years material warranty against delamination and mildew growth.

- Always prepare a mock-up of minimum 4' x 4' for approval prior to application to subject wall areas. The mock-up serves two purposes, to establish coverage and material requirements and to establish owner's expectations as to the appearance of the texture. Coverage varies according to substrate conditions and applicator technique and skill level.
- The application instructions described herein represent the most typical methods currently used, but are in no way intended to restrict the designer, contractor or faux finisher in terms of creating new patterns, effects or textures using PermaTone products. Instructions as to surface preparation and reduction should be followed precisely, however, in order not to void the warranty.
- PermaTone products should never be mixed with other materials, with the exception of clean, potable water, and then only where indicated as acceptable in this or other PermaTone product information documents.
- Information contained in this bulletin conforms to the standard detail recommendations and specifications for the installation of PermaTone products, is presented in good faith, and is applicable as of the date of this document. PermaTone assumes no liability, expressed or implied, as to the architecture, engineering, or workmanship of any project.
- Most equipment described in this document may be purchased from PermaTone or its distributors.

CorevMix