



Support Product

Description

An acrylic, vapor permeable interior paint.

Recommended Use

Interior commercial, military, educational and residential applications; used as a base for PermaTone Walltextures.

Colors

All custom; no limitations.

Packaging

1 gallon pail: 10 lbs. net, 10.7 lbs. gross; 5 gallon pail: 54 lbs. net, 56.8 lbs. gross.

Approximate Coverage

700-900 ft² per 5 gallon bucket.

Equipment

Brush, roller or spray equipment.

Surface Preparation

Surfaces must be clean, dry and free of dust, grease or loose material.

Application Instructions

May be applied with brush, roller or spray equipment. Allow to dry 12 hours prior to application of texture.

Properties

Initial set in 2 hours, cure in 24 hours, at 70°F and 50% RH.

Benefits

Water based; environmentally safe; vapor permeable; highly mildew resistant; excellent bonding surface.

Limitations

Skilled application required; not compatible with solvent based products or cleaners; apply in temperatures between 60°F and 85°F; protect face and eyes; use in well ventilated areas; for use on interior wall and ceiling surfaces only; do not mix with other products; prepare metal surfaces such as corner bead with rust inhibitor prior to application of Pintufondo.

Maintenance

See Application guidelines for PermaTone Walltextures for information on maintenance.

Warranty

10 years material warranty against delamination, color fading and mildew growth.

- Always prepare a mock-up of minimum 4' x 4' for approval prior to application to subject wall areas. The mock-up serves two purposes, to establish coverage and material requirements and to establish owner's expectations as to the appearance of the texture. Coverage varies according to substrate conditions and applicator technique and skill level.
- The application instructions described herein represent the most typical methods currently used, but are in no way intended to restrict the designer, contractor or faux finisher in terms of creating new patterns, effects or textures using PermaTone products. Instructions as to surface preparation and reduction should be followed precisely, however, in order not to void the warranty.
- PermaTone products should never be mixed with other materials, with the exception of clean, potable water, and then only where indicated as acceptable in this or other PermaTone product information documents.
- Information contained in this bulletin conforms to the standard detail recommendations and specifications for the installation of PermaTone products, is presented in good faith, and is applicable as of the date of this document. PermaTone assumes no liability, expressed or implied, as to the architecture, engineering, or workmanship of any project.
- Most equipment described in this document may be purchased from PermaTone or its distributors.

Pintufondo