



## Support Product

### Description

A clear, acrylic, permeable, mildew resistant primer sealer.

### Recommended Use

Interior commercial, hospitality, military, educational and residential applications; for sealing new or previously painted masonry or drywall surfaces; acts as a bonding primer on substrates such as ceramic tile, glazed brick, non-ferrous metal surfaces, and mildew damaged drywall.

### Colors

Milky blue-white.

### Packaging

5 gallon pail: 36 lbs. net, 38.8 lbs. gross.

### Approximate Coverage

1000-1200 ft<sup>2</sup> per 5 gallon bucket.

### Equipment

May be brush or roller applied. Spray application is not recommended.

### Surface Preparation

Surfaces must be clean, dry and free of dust, grease or loose material.

### Application Instructions

Apply Sottofondo uniformly with brush or roller. Allow to dry 24 hours before applying top coat.

### Properties

Initial set in 2 hours, cure in 24 hours, at 70°F and 50% RH.

### Benefits

Water based; environmentally safe; smooth; vapor permeable; flexible; hard; low absorption.

### Limitations

Skilled application required; not compatible with solvent based products or cleaners; apply in temperatures between 60°F and 85°F; protect face and eyes; use in well ventilated areas; for use on interior wall and ceiling surfaces only; do not mix with other products; prepare metal surfaces such as corner bead with rust inhibitor prior to application of Sottofondo.

### Maintenance

See Application guidelines for PermaTone Walltextures for information on maintenance.

### Warranty

10 years material warranty against delamination and mildew growth.

- Always prepare a mock-up of minimum 4' x 4' for approval prior to application to subject wall areas. The mock-up serves two purposes, to establish coverage and material requirements and to establish owner's expectations as to the appearance of the texture. Coverage varies according to substrate conditions and applicator technique and skill level.
- The application instructions described herein represent the most typical methods currently used, but are in no way intended to restrict the designer, contractor or faux finisher in terms of creating new patterns, effects or textures using PermaTone products. Instructions as to surface preparation and reduction should be followed precisely, however, in order not to void the warranty.
- PermaTone products should never be mixed with other materials, with the exception of clean, potable water, and then only where indicated as acceptable in this or other PermaTone product information documents.
- Information contained in this bulletin conforms to the standard detail recommendations and specifications for the installation of PermaTone products, is presented in good faith, and is applicable as of the date of this document. PermaTone assumes no liability, expressed or implied, as to the architecture, engineering, or workmanship of any project.
- Most equipment described in this document may be purchased from PermaTone or its distributors.

# Sottofondo