

PermaTone[®]
by  **COREV**[®]

Corevmix



PermaTone® Corevmix

Corevmix A permeable, finely ground, acrylic, base leveler material for interior walls.

RECOMMENDED USE

The acrylic base provides hardness, low absorption and adhesion to diverse surfaces. It is a smooth, breathable and flexible base for PERMATONE finishes or painted surfaces.

COVERAGE

Each 5 gal. pail provides 200-220 ft² of coverage.

Max. thickness wet: 30 mils per coat.

PACKAGING

1 gal. pail: 11.5 lbs. net, 11.9 lbs. gross

5 gal. pail: 60 lbs. net, 62.8 lbs. gross

PROPERTIES

Drying Time

Initial Set: 4 hrs. @ 77°F, 50% RH

Cure: 24 hrs. @ 77°F, 50% RH

REDUCTION

Use potable water. Don't exceed 10% by volume.

EQUIPMENT

- Stainless steel trowels or spatulas
- Sandpaper #180 to #400 depending on selection of the top coat material

APPLICATION

Surface Preparation

Surface must be clean, dry and free of dust, grease or other materials that may affect bonding.

Previously painted surfaces must be scraped to remove all loose paint.

Material Preparation

Mix COREVMIX to a homogeneous consistency for 30 seconds with a mud mixer at low speed.

Application Procedures

Apply COREVMIX with a stainless steel trowel. Allow the product to dry 4 to 6 hours and apply as many layers as needed.

When product is dry, sand the surface smooth as necessary.

Remove any residual dust before applying other materials.

STORAGE

Store COREVMIX in its original container at temperatures not less than 40°F (4°C) or greater than 110°F (43°C). Store in covered space, out of direct sunlight. Do not stack pails more than three high.

SHELF LIFE

Approximately one year if stored properly.

WARRANTY

COREVMIX is conditionally warranted for 10 years against delamination and mildew growth. FOR COMPLETE INFORMATION, CONSULT PERMATONE'S LONG FORM SPECIFICATIONS AND PRODUCT WARRANTIES. This warranty does not apply to any party constituting a "consumer" for purposes of the Magnuson-Moss Warranty Act. All other warranties, whether expressed or implied, including without limitation any warranty of merchantability or fitness for purpose are expressly disclaimed.

LIMITATIONS

- Do not use for exterior application.
- Do not mix with other products.
- Exceeding 30 mils thickness in a single layer may cause surface cracking.
- Surface air and substrate temperatures must be 40°F or higher during application and for a period of 24 hours thereafter.
- COREVMIX is not compatible with solvent base products or cleaners.
- Use in well ventilated areas. Protect all adjacent surfaces, door frames, windows, etc.) Do not water down material. Prepare metal surfaces such as corner bead within rust inhibitors prior to COREVMIX application.
- This product requires skilled application
- Wear eye and face protection during application.



PermaTone, Inc.
11620 Brittmoore Park Drive
Houston, Texas 77041
713/937-3437 TEL
713/937-9765 FAX
800/944-4911 TOLL FREE
www.permatone.com

PermaTone, the PermaTone logo, Corev, and the Corev logo are registered trademarks of Corev, Inc.